





得豐實業有限公司

Df Wisdom Industrial CO., LTD

HPG-N4-面板式電子手輪(Manual Pulse Generator)

· 輪盤徑 80 mm

DIMENSION



ELECTRICAL SPEC 電器規格

Detection System 檢測系統	Incremental 增量型
Output Wave 輸出波形	Square Wave 方波
Standard Number of Pulse Per Revolution 解析	25, 100
Output Phase 輸出相	AB phase
Electronics 電路特性	NPN Voltage 電壓型 and Line Driver 差動式
Power Supply 供應電源	DC 8 ~ 26V, DC 5V fixed
Current Consumption 消耗電流	< 60mA
Output Capacity 輸出容量	Sync. Current : 20mA, Residual Voltage : 0.5V or less
Max. Response 最大響應頻率	10K Hz
Phase Different 相位差	A, B phase different 90° ± 45° (T/4 ± T/8)
Wave Form Rise / Fall 波形上下時間	2 μs or less

MECHANICAL SPEC 機械規格


Shaft Loading 軸荷重	Axial 軸向 : 1 kg, Radial 徑向 : 2 kg
Starting Torque(at 25°C) 起動轉矩	> 600 g
Max. Speed 最大機械容許轉速	6000 rpm (Maximum 瞬間容許速度) 200 rpm (Continuous 連續容許速度)
X.Y.Z. Vibration 震動	10 ~ 50 Hz / 1.5 mm X.Y.Z. 2Hr
Shock 衝擊	50 g per 11 ms
Rotational Life 迴轉壽命	10 ⁶ cycles (200 rpm)
Weight 重量	≤ 400 g

ENVIRONMENTAL SPEC 環境規格


Operating Temp./ Humidity 操作溫度/濕度	-10°C ~ 60°C, RH 35 % ~ 90 % (No Condensation)
Storage Temp. 儲存溫度	-20°C ~ 80°C

Output Wave Form 輸出波形 (Clockwise rotation is "CW Rotation" lookwd from the front side)

NPN Voltage / NPN Open Collector



Line Driver



· P = 1P/R : a.b.c.d = P/4 ± P/6
 · C.P = click point 停止點信號
 (For 25 P/R, C.P is at each position of a.b.c.d. 25 PPR 的停止點信號在 a.b.c.d 各個位置)
 Point e is recommended as the system switching timing.
 e 點為建議信號讀取/切換的範圍。

Specifications Model 規格 型號

HPG-N4- -

Pulse per Revolution

解析
 25 : 25 PPR
 100 : 100 PPR

Electronics & Supply Voltage

電路特性 & 供應電源
 V : NPN Voltage 8 ~ 26Vdc
 V5 : NPN Voltage 5Vdc
 L : Line Driver 5Vdc
 HL : Line Driver 5 ~ 26Vdc
 C : NPN Open Collector 5 ~ 26Vdc

Electrical Connection 接線圖

