



得豐實業有限公司

Dfwisdom Industrial CO., LTD

SGB-C 鋼片型/夾緊式/短型撓性聯軸器 Disk / Clamp Type / Shorter of Flexible Coupling



材質 | Material

鋁合金 Aluminum alloy

緩衝材: 不銹鋼彈片

Buffer material: SUS disk

表面處理 | Surface Treatment

陽極處理 Anodizing standard white


特性 | Features

1. 高剛性
2. 扭力大
3. 低慣性
4. 零背隙
5. 適用於工作母機、伺服馬達、
高精度傳動
6. 固定方式: 夾緊式

型號 d1/孔徑 d2/孔徑
Catalog Number Inside dia Inside dia

SGB-40C- X

- High rigid
- High torque
- Low inertia
- Zero backlash
- Suitable for working machine -
servomotor and high precision
transmission mechanism.
- Fixed mode: Clamp type



尺寸 Dimension

單位 / Unit : mm

Catalog Number 型號	D	B	I	F	L	M	d1xd2 標準孔徑(H7)		Mass** 重量(g)
							Min	Max	
SGB-40C	40	28	15	4.5	34.5	3-M4	8	16	88
SGB-45C	45	33	15	4.5	34.5	3-M4	8	18	100
SGB-50C	50	40	20	6.0	46	4-M5	10	20	188
SGB-57C	57	42	20	6.0	46	4-M5	12	25	205
SGB-65C	65	50	24	7.0	55	4-M6	12	28	368

規格特性 Specifications Characteristics

單位 / Unit : mm

Catalog Number 型號	Ratad Torque 一般扭力 (N . m)	Max Torque 最大扭力 (N . m)	Max Rotational Frequency最高 回轉速(rpm/min)	Moment* of inertia 慣性 (kg . m ²)	Errors of Eccentricity 容許偏心(mm)	Errors of Angularity 容許偏角(°)	Errors of Shaft End-Play容許 軸向位差(mm)
SGB-40C	6	12	10000	17x10 ⁻⁶	0.02	1.0	±0.25
SGB-45C	9	18	10000	23x10 ⁻⁶	0.02	1.0	±0.30
SGB-50C	17	34	10000	48x10 ⁻⁶	0.02	1.0	±0.30
SGB-57C	25	50	10000	76x10 ⁻⁶	0.02	1.0	±0.40
SGB-65C	55	110	10000	185x10 ⁻⁶	0.02	1.0	±0.40